


14,4 W - 180 STRIP LED



CODE	Watt/M	Temp.	Lumen	CRI	Led/m	V input	✂	mm	IP
B01N118	14.4 W	2700°K	1026	90	180	24Vcc	33mm	10x2	IP20
B01N127	14.4 W	3000°K	1031	90	180	24Vcc	33mm	10x2	IP20
B01N128	14.4 W	4000°K	1100	90	180	24Vcc	33mm	10x2	IP20
B01N129	14.4 W	6000°K	1150	90	180	24Vcc	33mm	10x2	IP20
B01R059	14.4 W	2700°K	1026	90	180	24Vcc	33mm	10x3	IP65
B01R066	14.4 W	3000°K	1031	90	180	24Vcc	33mm	10x3	IP65
B01R067	14.4 W	4000°K	1100	90	180	24Vcc	33mm	10x3	IP65
B01R068	14.4 W	6000°K	1150	90	180	24Vcc	33mm	10x3	IP65

DISEGNO TECNICO TECHNICAL DRAWING:

SERVIZI DISPONIBILI SU RICHIESTA:
SERVICES ON DEMAND:

Bobina 50 m IP20
Roll 50 m IP20
Bobina 25 m IP65
Roll 25 m IP65



Spezzonatura
Customized cutting lenght



Saldatura cavi
Soldering wires



Applicazione connettori
Connectors Applying



Controllo personalizzato
Customized checking



3 Step MacAdam

CERTIFICAZIONI / CERTIFICATIONS:

