


9,6 W STRIP LED



CODE	Watt/M	Temp.	Lumen	CRI	Led/m	V input	✂	mm	IP
B01N012B	9,6 W	2700°K	740	90	120	12Vcc	25 mm	8x2	IP 20
B01N013	9,6 W	3000°K	745	90	120	12Vcc	25 mm	8x2	IP 20
B01N014	9,6 W	4000°K	770	90	120	12Vcc	25 mm	8x2	IP 20
B01N016	9,6 W	6000°K	780	90	120	12Vcc	25 mm	8x2	IP 20
B01R012B	9,6 W	2700°K	740	90	120	12Vcc	25 mm	8x3	IP 65
B01R013	9,6 W	3000°K	745	90	120	12Vcc	25 mm	8x3	IP 65
B01R014	9,6 W	4000°K	770	90	120	12Vcc	25 mm	8x3	IP 65
B01R016	9,6 W	6000°K	780	90	120	12Vcc	25 mm	8x3	IP 65

DISEGNO TECNICO TECHNICAL DRAWING:

SERVIZI DISPONIBILI SU RICHIESTA:
SERVICES ON DEMAND:

Bobina 50 m IP 20 - Bobina 25 m IP 65
Roll 50 m IP 20 - Roll 25 m IP 65



Spezzonatura
Customized cutting lenght



Saldatura cavi
Soldering wires



Applicazione connettori
Connectors Applying



Controllo personalizzato
Customized checking

24^{Vcc}

Disponibile / Available



3 Step MacAdam

CERTIFICAZIONI / CERTIFICATION:

CE cULus III RoHS TÜV A+