



CRI 97 STRIP LED



CODE	Watt/M	Temp.	Lumen	CRI	Led/m	V input		mm	IP
B05N004	23 W	2700°K	1620	97	120	24 Vcc	50mm	10x2	IP20
B05N008	23 W	3000°K	1630	97	120	24 Vcc	50mm	10x2	IP20
B05N005	23 W	4000°K	1730	97	120	24 Vcc	50mm	10x2	IP20
B05N006	23 W	6000°K	1820	97	120	24 Vcc	50mm	10x2	IP20
B05R004	23 W	2700°K	1620	97	120	24 Vcc	50mm	10x3	IP65
B05R008	23 W	3000°K	1630	97	120	24 Vcc	50mm	10x3	IP65
B05R005	23 W	4000°K	1730	97	120	24 Vcc	50mm	10x3	IP65
B05R006	23 W	6000°K	1820	97	120	24 Vcc	50mm	10x3	IP65

Abbinabile con profilo: vedi tabella pag. 25

DISEGNO TECNICO TECHNICAL DRAWING:



SERVIZI DISPONIBILI SU RICHIESTA:

SERVICES ON DEMAND:

-  Bobina 50 m IP20
Roll 50 m IP20
-  Bobina 25 m IP65
Roll 25 m IP65
-  Spezzatura
Customized cutting lenght
-  Saldatura cavi
Soldering wires
-  Applicazione connettori
Connectors Applying
-  Controllo personalizzato
Customized checking
-  3 Step MacAdam

CERTIFICAZIONI / CERTIFICATIONS:

