


HE 180 LED STRIP LED



CODE	Watt/M	Temp.	Lumen	CRI	Led/m	V input	✂	mm	IP
B01N137	19,2 W	2700°K	3260	90	180	24Vcc	50mm	10x2	IP20
B01N138	19,2 W	3000°K	3450	90	180	24Vcc	50mm	10x2	IP20
B01N139	19,2 W	4000°K	3680	90	180	24Vcc	50mm	10x2	IP20
B01N140	19,2 W	6500°K	3840	90	180	24Vcc	50mm	10x2	IP20
B01R071	19,2 W	2700°K	3260	90	180	24Vcc	50mm	10x2	IP65
B01R072	19,2 W	3000°K	3450	90	180	24Vcc	50mm	10x2	IP65
B01R073	19,2 W	4000°K	3680	90	180	24Vcc	50mm	10x2	IP65
B01R074	19,2 W	6500°K	3840	90	180	24Vcc	50mm	10x2	IP65

Abbinabile con profilo: vedi tabella pag. 25

DISEGNO TECNICO TECHNICAL DRAWING:

SERVIZI DISPONIBILI SU RICHIESTA:
SERVICES ON DEMAND:

Lunghezza massima 3 m
Maximum length 3 m



Bobina 50 m IP20
Roll 50 m IP20
Bobina 25 m IP65
Roll 25 m IP65



Spezzonatura
Customized cutting lenght



Saldatura cavi
Soldering wires



Applicazione connettori
Connectors Applying



Controllo personalizzato
Customized checking



3 Step MacAdam

CERTIFICAZIONI / CERTIFICATIONS:

