

HE 19,2 W STRIP LED



CODE	Watt/M	Temp.	Lumen	CRI	Led/m	V input		mm	IP
B01N096	19,2 W	2700°K	3000	90	112	24Vcc	71,4mm	10x2	IP20
B01N023	19,2 W	3000°K	3050	90	112	24Vcc	71,4mm	10x2	IP20
B01N099	19,2 W	4000°K	3150	90	112	24Vcc	71,4mm	10x2	IP20
B01N025	19,2 W	6000°K	3250	90	112	24Vcc	71,4mm	10x2	IP20
B01R060	19,2 W	2700°K	3000	90	112	24Vcc	71,4mm	10x3	IP65
B01R061	19,2 W	3000°K	3050	90	112	24Vcc	71,4mm	10x3	IP65
B01R062	19,2 W	4000°K	3150	90	112	24Vcc	71,4mm	10x3	IP65
B01R063	19,2 W	6000°K	3250	90	112	24Vcc	71,4mm	10x3	IP65

Abbinabile con profilo: vedi tabella pag. 25

DISEGNO TECNICO TECHNICAL DRAWING:



SERVIZI DISPONIBILI SU RICHIESTA:
SERVICES ON DEMAND:

-  Bobina 50 m IP20
Roll 50 m IP20
-  Bobina 25 m IP65
Roll 25 m IP65
-  Spezzonatura
Customized cutting lenght
-  Saldatura cavi
Soldering wires
-  Applicazione connettori
Connectors Applying
-  Controllo personalizzato
Customized checking
-  3 Step MacAdam

CERTIFICAZIONI / CERTIFICATIONS:

