


19,2 W - 240 STRIP LED



CODE	Watt/M	Temp.	Lumen	CRI	Led/m	V input	✂	mm	IP
B01N044B	19,2 W	2700°K	1565	90	240	24Vcc	25mm	10x2	IP20
B01N047	19,2 W	3000°K	1570	90	240	24Vcc	25mm	10x2	IP20
B01N046	19,2 W	4000°K	1600	90	240	24Vcc	25mm	10x2	IP20
B01N048	19,2 W	6000°K	1650	90	240	24Vcc	25mm	10x2	IP20
B01R064	19,2 W	2700°K	1565	90	240	24Vcc	25mm	10x3	IP65
B01R065	19,2 W	3000°K	1570	90	240	24Vcc	25mm	10x3	IP65
B01R069	19,2 W	4000°K	1600	90	240	24Vcc	25mm	10x3	IP65
B01R070	19,2 W	6000°K	1650	90	240	24Vcc	25mm	10x3	IP65

DISEGNO TECNICO TECHNICAL DRAWING:



SERVIZI DISPONIBILI SU RICHIESTA: SERVICES ON DEMAND:



Bobina 50 m IP 20
Roll 50 m IP 20



Spezzatura
Customized cutting lenght



Saldatura cavi
Soldering wires



Applicazione connettori
Connectors Applying



Controllo personalizzato
Customized checking



3 Step MacAdam

CERTIFICAZIONI / CERTIFICATION:

CE III RoHS TÜV A*